



FML ske Manufacturing Co., Ltd



30 mm x 55 mm x 13 mm SNR MLE7006CVUJ74S angular contact ball bearings

Bearing No. MLE7006CVUJ74S

MLE7006CVUJ74S Bearing 2D drawings and 3D CAD models

Size	30x55x13 mm
Bore Diameter	30 mm
Outer Diameter	55 mm
Width	13 mm
d	30 mm
D	55 mm
B	13 mm
C	13 mm
Angle (°)	15 °
d1	38.1 mm
d2	36.15 mm
D1	48.55 mm
D2	50.15 mm
a	13 mm
Contact angle	17 °
rs min	1 mm
r1s min	0.6 mm
f0	7.98
Precision class	P4S
Mass	0.11 kg
Dynamic load, C	8.1 kN
Static load, C0	4.7 kN
Fatigue limit load, Cu	0.27 kN
Nlim (grease)	38,000 rpm
Axial displacement K Factor	1.38



FML ske Manufacturing Co., Ltd

Preload level	7
Preload value	0.04 kN
Axial rigidity	35 N/ μ m
Radial rigidity	175 N/ μ m
Min operating temperature, T _{min}	-20 ° C
Max operating temperature, T _{max}	120 ° C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.38 Hz
Characteristic outer ring frequency, BPF0	8.73 Hz
Characteristic inner ring frequency, BPFI	11.27 Hz
da min	35.5 mm
db min	35.5 mm
Da max	49.5 mm
Db max	49.5 mm
r1a max	0.6 mm
ra max	1 mm
D6	40.1 mm